

# LANE MOUNTAIN COMPANY LM FOOTING SAND



## DATA SHEET

### Product Description

*Finely blended silica sand with ideal sizing and compaction for new or existing horse arenas*

### Screen Analysis (Typical) – individual results will vary

<i>% Retained 30 mesh:</i>	<i>0.2%</i>
<i>% Retained 40 mesh:</i>	<i>3.3%</i>
<i>% Retained 50 mesh:</i>	<i>9%</i>
<i>% Retained 70 mesh:</i>	<i>11%</i>
<i>% Retained 100 mesh:</i>	<i>17.5%</i>
<i>% Retained 140 mesh:</i>	<i>35%</i>
<i>% Retained 200 mesh:</i>	<i>14%</i>
<i>% Retained PAN:</i>	<i>10%</i>

### Physical Properties (Typical)

<i>Color:</i>	<i>White/Off White</i>
<i>Specific gravity:</i>	<i>2.65</i>
<i>Moisture:</i>	<i>8-12%</i>

### For more information on our products, please contact:

*Lane Mountain Company  
Tim Hemphill, VP  
206-941-4996 (cell)  
tim@lanemt.com*

*Production Facility:  
Lane Mountain Company  
3119 Highway 231  
Valley, WA 99181  
509-937-2221*

*The data above is based on average results on production samples. Product shipments are subject to normal variation. Test data does not guarantee minimum or maximum specifications.*